



Model: [7590](#)
Multiple Gun Pressure Unloader

Specs

Max Flow:	52 gpm
Min Pressure:	400 psi
Max Pressure:	2175 psi
Inlet Port Size:	1
Discharge Port Size:	1
Type of Accessory:	Unloader
Material:	Brass (BB)

Description:

This Pressure Sensitive Regulating Unloader is designed for single or multiple pump, weep or multi-nozzle systems. This unloader maintains set system pressure and goes into by-pass with the release of the trigger or an obstruction downstream. Pressure is held in the line during by-pass with full pressure when the gun is opened or the obstruction cleared and minimal pressure fluctuation with the alternating use of multiple guns. 5-10% by-pass is necessary for optimum performance. Minimum 10 GPM per gun.

Accessory to be used with these Pumps:

[2520](#) 25 FRAME PISTON PUMP



[2520C25](#) FRAME PISTON PUMP



[3520C](#)35 FRAME FLUSHED PLUNGER PUMP

[3520](#)35 FRAME PLUNGER PUMP

[3545](#)35 FRAME PLUNGER PUMP



[3535](#) 35 FRAME PLUNGER PUMP

[2530ALT](#) 25 FRAME PLUNGER PUMP



[6040](#)60 FRAME PISTON PUMP



[5CP5140CSS](#) 5CP PLUNGER PUMP



[2530.44101](#)25 FRAME PLUNGER PUMP - TEG