



The Pumps with Nine Lives



Model: [990857](#)
Flexible Discharge Hose

Specs

Max Flow:	25 gpm
Min Pressure:	100 psi
Max Pressure:	6000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.7
Type of Accessory:	Flexible Discharge Hose
Material:	Stainless Steel (SS)

Description:

Flexible hose should be installed in the discharge line prior to any hard plumbing. Excessive elbows, tees and hard plumbing can cause restrictions and liquid acceleration loss and result in excessive vibration and water hammering and damage within the pump.

Accessory to be used with these Pumps:

- [5CP31205CP](#) PLUNGER PUMP
- [5CP3120CSS5CP](#) PLUNGER PUMP
- [156015](#) FRAME PLUNGER PUMP
- [781K8](#) FRAME BLOCK-STYLE PLUNGER PUMP
- [59OBSOLETE 7](#) FRAME PLUNGER PUMP
- [455](#) FRAME PLUNGER PUMP
- [45G15FR](#) PUMP WTH GEARBOX
- [567](#) FRAME PLUNGER PUMP
- [59G1OBSOLETE 7FR](#) PUMP WITH GEARBOX
- [60G17FR](#) PUMP WTH GEARBOX
- [5CP3120CSSG15CP](#) PUMP WITH GEARBOX
- [5CP5140CSSG15CP](#) PUMP WITH GEARBOX
- [4SF35GS14SF](#) DIRECT DRIVE PLUNGER PUMPS
- [4SF40GS14SF](#) DIRECT DRIVE PLUNGER PUMPS
- [7818](#) FRAME BLOCK-STYLE PLUNGER PUMP
- [4SF40ELS4SF](#) DIRECT DRIVE PLUNGER PUMPS
- [5CP3120ALT5CP](#) PLUNGER PUMP
- [5CP3105CSS5CP](#) PLUNGER PUMP
- [607](#) FRAME PLUNGER PUMP
- [577](#) FRAME PLUNGER PUMP
- [781ALT8](#) FRAME BLOCK-STYLE PLUNGER PUMP
- [66DX30G166DX](#) DIRECT DRIVE PLUNGER PUMPS
- [66DX35G166DX](#) DIRECT DRIVE PLUNGER PUMPS
- [66DX40G166DX](#) DIRECT DRIVE PLUNGER PUMPS
- [4SF32ELS4SF](#) DIRECT DRIVE PLUNGER PUMPS