

Kanaflex®

KANAPOWER AT

for
MICRO
TUNNELING



Kanapower AT is our new abrasion resistant suction and discharge hose designed for demanding applications such as slurry systems in *micro-tunneling applications and directional boring*. Constructed of SBR rubber blended with static dissipating carbon black, it is rated to 140 P.S.I.

Kanaflex®

KANAPOWER AT

Lightweight... up to 50% lighter than conventional rubber hose

Extra heavy duty exposed helix... acts as a scuff guard, permits water to flow underneath, allows easy drag and provides substantial protection from outside impact and abrasion

Braided reinforcement... permits use under high working pressure

Smooth bore... provides unrestricted flow

Heavy duty sidewall... constructed of abrasion resistant static dissipating SBR rubber

Flexible... lends itself to working in much tighter spaces than conventional rubber hose



SPECIFICATIONS: KANAPOWER AT

SIZE	OUTSIDE DIAMETER Inches	PITCH Inches	MIN. BENDING RADIUS 72°F, Inches	WORKING PRESSURE 72°F, P.S.I.	BURSTING PRESSURE 72°F, P.S.I.	VACUUM RATING 72°F, In./Hg.	WEIGHT Lbs./Ft.
3"	3.90	0.59	8.0	140	700	28	1.65
4"	5.04	0.65	10.0	140	700	28	2.85
6"	7.26	0.87	16.0	140	700	28	4.50

Kanaflex®
CORPORATION

800 Woodlands Parkway
Vernon Hills, IL 60061

DISTRIBUTED BY: