Novaflex

5331/5332 Material Handling Hose





Part No. I.D. 0.D. **Plies** LBS/FT psi 5331BS-04500-00 4½ 5.73 3/8 4 150 5.45 5331BS-06000-00 6 7.25 4 150 3/8 7.51 150 9.26 5331BS-06625-00 6 5/8 8.07 3/8 6 5331BS-08625-00 8 5/8 10.19 3/8 8 150 12.97 5331RS-10750-00 12 50 8 150 17.83 1/2 8 150 22.80 5331BS-12775-00 123/4 14.55 1/2 5331BS-14000-00 16.04 1/2 12 150 27.21

1/2

12

18.04

Novaflex 5331

Dredge Sleeves/Sand Discharge Hose

A specially compounded abrasive resistant and static conductive tube. This hose is manufactured to very close O.D. tolerances

Construction:

Tube: Black abrasion resistant synthetic rubber.

Reinforcement: Polyester tire cord.

Cover: Black abrasion and weather resistant synthetic rubber.

Length: 20 ft.

Temperature Range: up to 180°F

Novaflex 5332 **Sand Suction Hose**

A specially compounded abrasive resistant and static conductive tube. This hose is manufactured to very close O.D. tolerances.

Construction:

Tube: Black abrasion resistant synthetic static conductive rubber.

Reinforcement: Polyester tire cord with helix wire.

Cover: Smooth black abrasion and weather resistant synthetic

rubber. Length: 20 ft.

Temperature Range: up to 180°F

Part No.	I.D.	0.D.	Tube Gauge	Plies	WP psi	WT LBS/FT
5332BS-04000-00	4	5.54	3/8	4	150	6.75
5332BS-04500-00	41/2	5.95	3/8	4	150	7.46
5332BS-06000-00	6	7.57	3/8	4	100	11.37
5332BS-06625-00	6 5/8	8.20	3/8	4	100	12.41
5332BS-08000-00	8	9.64	3/8	6	100	15.86
5332BS-08625-00	8 5/8	10.32	3/8	6	100	16.87
5332BS-10000-00	10	12.06	1/2	6	100	25.42
5332BS-10750-00	103/4	12.86	1/2	6	100	22.06
5332BS-12000-00	12	14.11	1/2	6	100	30.55
5332BS-12750-00	123/4	14.86	1/2	6	100	32.29
5332BS-14000-00	14	16.37	1/2	8	100	42.66

Whitby, ON Indianapolis, IN Tel 317.334.1444 Haw River, NC Berlin, NJ

5331BS-16000-00 16

Tel 905.666.4970 Tel 336.578.2161 Tel 856.768.2275

Fax 905.666-9388 Fax 317.334.1535 Fax 336-578.5554

Fax 856.768.2385

30.82

800.526.6288 800.334.4270 800.225.0215



Email: sales@novaflex.com Website: www.novaflex.com