

TPU Vacuum Hose



Heavy Duty Vacuum Hose

Designed specifically for transfer of abrasive materials under vacuum from storage tanks barges and tankers, including underwater applications in aquaculture; hatchery, pen transfer, stream release.

Light-weight alternative to heavy walled PVC

- Polyurethane wall for abrasion resistance and maximum product flow
- All weather construction, resistant to ozone attack and ultra-violet
- Smooth inner tube for maximum product flow
- External wear strip prevents damage from abrasion
- Resistant to salt for under water applications
- Available with an embedded copper static wire that allows the hose to be grounded, eliminating the build up of static electricity during material transfer

Heavy duty construction for full vacuum. Available in diameters from 3" to 8".

Style	I.D.	O.D.	Bend Radius	Neg pressure (Inch Hg)	Pos.W.P PSI	Pitch	Wall Gauge (thou")	Weight lbs/ft
SFTPUX04FV	4"	4.45"	9.5"	25"	35	.75"	0.07	1.66
SFTPUX06FV	6"	6.65"	14"	25"	30	.75"	0.07	2.5
SFTPUX08FV	8"	8.85"	14"	25"	30	1.00"	0.085	3.4

(Larger sizes available upon request)

Temperature range -50°F to +200°F Rated for full vacuum

Berlin, NJ	Tel 856.768.2275	Fax 856.768.2385	800.225.0215
Indianapolis, IN	Tel 317.334.1444	Fax 317.334.1535	800.526.6288
Haw River, NC	Tel 336.578.2161	Fax 336-578.5554	800.334.4270
Ajax, ON	Tel 905.686.5200	Fax 905.686.8349	

THE
NOVAFLEX[®]
GROUP 

Email: sales@novaflex.com
Website: www.novaflex.com

All products are warranted to be free from all defects in material and workmanship. It is impossible to test all products under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all products under the conditions that duplicate the service conditions prior to installation. All improvements, all specifications are subject to change without prior notice. It is the buyer and/or end users' responsibility to review our complete **Terms and Conditions of Sale** located on our web sites at: www.novaflex.com / www.z-flex.com / www.flexmaster.com.