

# Novaflex®

## U-Lok 101

### U-Lok 101

A combination of high quality material and economical price provide and excellent flexible duct. PVC coated duct provides an alternative for wet fumes

#### Applications

Dust control  
Air movement  
General service  
Fume Control

#### Specifications

Product code: 3UL101X  
Material: Fiberglass/PVC coated  
Construction: Mechanical bond, corrosion resistant helix  
Diameters: 2" to 24". Larger sizes available  
Bend radius: = 1.5 x I.D.  
Weight: 6" I.D. = .9 lbs/ft  
Length: 25ft  
Compression ratio: 6:1  
Temperature range: -20° F (-29°C) to +250°F (121°C)  
Colour: Black



### Specification Chart

I.D.	2	3	4	5	6	8	10	12
Working Pressure/PSI	-	4.3	4	3.6	3.5	3	2.15	1.8
Negative Pressure Inch. H.g	-	3.2	2.7	2.4	2.2	1.8	1.6	1.25

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

09.2011

#### IN USA

##### North Carolina

449 Trollingwood Road  
Haw River, NC 27258  
tel (336)578-2161  
fax (336)578-5554  
800-334-4270

##### New Jersey

1024 Industrial Drive  
West Berlin, NJ 08091  
tel (856)768-2275  
fax (856)768-2385  
800-225-0215

##### Indianapolis

7812 Moller Road  
Indianapolis, IND 46268  
tel (317)334-1444  
fax (317)334-1535  
800-526-6288

#### IN CANADA

##### Ajax, Ontario

555 Beck Crescent  
Ajax, ON L1Z 1C9  
tel (905)686-5200  
fax (905) 686.8349  
800-563-3539

#### IN U.K.

##### Bromborough, Wirral

18 Candy Park 2, Power Road  
Bromborough, Wirral UK CH62 3QT  
tel 44(0)151-334-0873  
fax 44(0)151-334-7145  
www.novaflex.co.uk Email: sales@novaflex.co.uk