

U-Lok 1030 Heavy Duty Service

U-Lok 1030

Heavy Duty Service Ducting(30 mil Urethane Duct)

This extra heavy duty service duct will stand up to the toughest jobs. Constructed of 30 mil urethane, with an extra wide helix for added scuff resistance and strength. Great flexibility.

Applications

Heavy duty abrasion resistance
Leaf collection
Material handling, woodworking
High flexibility. Oil resistant
U.V. stabilized
Meets FDA requirements 177.2600

Construction

Product code: 3UL1030
Material: Urethane, 30 mil, mechanical lock corrosion resistant helix
Diameters: 4" to 14".
Weight: 6" I.D. = 1.9 lbs/ft
Colour: Black
Compression Ratio: 4:1.
Length 25 ft
Temperature Range: -20°F (-29°C) to +250°F (121°C)



I.D.	4	5	6	8	10	12
Working Pressure/ PSI	18	18	16	16	14	14
Negative Pressure Inch. H.g	26	21	16	6	5	4.5

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

Due to continuous improvements, technical data subject to change without notice

03.2011

Bromborough, UK Tel 44.0151.334.0873 Fax 44.0151.334.7145
Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
GROUP 

Email: sales@novaflex.com
Website: www.novaflex.com