

Novaflex U-Lok 1100

Fume Control Service



U-Lok 1100

For superior fume control Novaflex offers a range of ultra high performance material. Even the most noxious fumes can be contained to meet today's stringent health and environmental requirements. Novaflex U-Lok 1100 is an extremely versatile combination of fiberglass and PTFE. Ultra flexible for tight bends.

Applications

Highly corrosive fumes
Hot exhaust
High temperature where silicone is not permitted
Resists over 3,000 chemicals
Diesel exhaust extraction where temperature permits.

**Not suitable for wet fumes*

Construction

Product Code: 3UL1100
Material: Fiberglass/PTFE coated
Construction: Mechanical bond, corrosion resistant helix
Diameters: 3" to 24" I.D. Larger sizes available
Bend Radius 1.5 x I.D.
Weight: 6" I.D. = .9 lbs/ft
Length: 25ft
Compression Ratio: 4:1
Temperature Range: -65°F to +500°F
Colour: Grey

I.D.	3	4	5	6	8	10	12
Working Pressure/PSI	5	3.75	3	2.3	1.4	1	.75
Negative Pressure Inch. H.g	3.2	2	1.5	1	.75	.4	.25

Due to continuous improvements, technical data subject to change without notice

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
GROUP

Email: sales@novaflex.com
Website: www.novaflex.com