

## Ulok 200 Medium Service Duct



### U-Lok 200

Medium weight flexible ducting. Heavier gauge fabric and coating to provide longer service life. Neoprene coating provides good cold temperature resistance compared with PVC. Manufactured with UL94V0 approved materials.

#### Applications

Heavy-duty dust control  
Outdoor plant clean-up  
Sawdust, hot air blower

#### Construction

Product code: 3UL200X  
Material: polyester/neoprene  
Construction: Mechanical bond, corrosion resistant  
Diameters: 3" to 24" I.D. Larger sizes available  
Bend radius: = 1.5 x I.D.  
Weight: 6" I.D. - 1.1 lbs/ft  
Length: 25ft  
Compression Ratio: 6:1  
Temperature Range: -65°F (-54°C) to +250°F (+121°C)  
Colour: Black

I.D.	3	4	5	6	8	10	12
Working Pressure/PSI	4.3	4	3.6	3.5	3	2.15	1.8
Negative Pressure. H.g.	3.2	2.7	2.4	2.2	1.8	1.6	1.25

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. Due to continuous improvements, technical data subject to change without notice.

Rev: 03.2011

**Berlin, NJ**  
**Indianapolis, IN**  
**Haw River, NC**  
**Ajax, ON**  
**Liverpool, UK**

Tel 856.768.2275

Tel 317.334.1444

Tel 336.578.2161

Tel 905.686.5200

Tel 44.151.334.0873

Fax 856.768.2385

Fax 317.334.1535

Fax 336.578.5554

Fax 905.686.8349

Fax 44.151.334.7145

800.225.0215

800.526.6288

800.334.4270

THE  
**NOVAFLEX**  
GROUP



Email: [sales@novaflex.com](mailto:sales@novaflex.com)

Website: [www.novaflex.com](http://www.novaflex.com)