

AF-1 Medium Service Duct



AF-1

With bonded construction and encapsulated wire, this duct is non-marking, lightweight and economical. Manufactured with UL94V-0 approved materials.

Applications

Air handling
Fume control
Dust collection
Cool air supply

Construction

Material: Polyester fabric, Neoprene coated
Construction: Single ply fabric over fully encapsulated spring steel wire
Diameters: 1.5" to 36"
Weight: 6" I.D. = .84 lbs/ft.
Length: 25 ft
Compression Ratio: 5:1
Temperature Range: -40° to +250°F
Color: Black

I.D.	2	3	4	5	6	8	10	12
Working Pressure/PSI	20	14	13	9	7	7	5	3
Negative Pressure Inch. H.g	11.7	11.3	10.5	6	4	2.5	1.75	1.25

Due to continuous improvements, technical data subject to change without notice

rev 09.2010

Indianapolis, IN
Haw River, NC
Berlin, NJ
Ajax, ON

Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Tel 905.686.5200 Fax 905.666.9388 800.563.3539

THE
NOVAFLEX
GROUP

Email: sales@novaflex.com
Website: www.novaflex.com