

CFB-PB10 SERIES MODIFIED MOLDED BLOCK CARTRIDGE

SEDIMENT FILTRATION AND CHLORINE TASTE & ODOR REDUCTION IN A SINGLE CARTRIDGE*



Features Fibredyne™ technology

The Pentair CFB-PB Cartridge is designed to reduce chlorine taste & odor, sediment and other substances.*

CFB-PB Cartridges are modified molded block manufactured using our proprietary Fibredyne technology. This technology creates a unique filter media by attaching powdered activated carbon and lead adsorbent material onto a cellulose-free synthetic fiber matrix. This results in higher reduction efficiencies that resist plugging, offers longer life, and features the lowest pressure drop over the effective life of the cartridge of any available 0.5-micron filter cartridge.*

Fibredyne carbon block technology also offers up to two times the chlorine taste & odor reduction and dirt holding capacity of traditional blocks.* In addition, this technology will not release fines into the effluent stream due to a unique post-filtration layer that is fused to the carbon/fiber media blend.

The CFB-PB Cartridge is an ideal choice for a wide range of residential, food service, commercial and industrial applications.

FEATURES/BENEFITS

Premium dirt holding capacity*
High chlorine taste & odor and bad taste and odor reduction*

SPECIFICATIONS

Filter Media – Bonded PAC
Endcaps – Polypropylene
Netting – Polyethylene

Gaskets – Santoprene
Temperature Rating –
40-180°F (4.4-82.2°C)



Tested and Certified by NSF International to NSF/ANSI Standard 42 for material requirements only.

*Not Tested or Certified by NSF

SPECIFICATIONS AND PERFORMANCE

MODEL #	PART #	MAXIMUM DIMENSIONS	RATING (NOMINAL)*	INITIAL ΔP (PSI) @ FLOW RATE (GPM)*	CHLORINE TASTE & ODOR REDUCTION @ FLOW RATE (GPM)*
CFB-PB10	255681-43	2.88" x 9.75" (73 mm x 248 mm)	0.5 micron	8.1 psi @ 1 gpm (0.56 bar @ 3.8 Lpm)	>5,000 gallons @ 1 gpm (> 18,927 L @ 3.8 Lpm)

*Not Tested or Certified by NSF

NOTES: Performance capacity depends on system design, flow rate and certain other application conditions. Cartridges may contain a very small amount of carbon fines (very fine black powder). After installation, follow the instructions for flushing the cartridge to remove the fines before using the water. You should flush the tap at least 20 seconds prior to using water for drinking or cooking purposes. This is particularly important if the tap has not been used daily. Micron ratings based on 85% or greater removal of given particle size. Estimated capacity using 2 ppm free available chlorine at 0.5 ppm breakthrough.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 USA
P: 262.238.4400 | WATERPURIFICATION.PENTAIR.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com

© 2018 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

310116 REV E JE18