



## Pressure Wash Reels

### Series 30000 / H18006 / PW - 10mm I.D.

Compact design and quality steel construction are incorporated into Reelcraft's newest line of pressure wash reels. The pressure wash reels are able to carry 100 to 300 feet of hose and are complete with a high pressure swivel for maximum product delivery.

CM6050HN



PW7650 OHP118

Model w/o Hose	Hose I.D.		Hose Capacity		Pressure bar	(F)NPTF Reel Outlet in	(F)NPTF Reel Inlet in	Dimensions (mm)			Shipping Weight kg*
	mm	in	mtr	ft				Length	Width	Height	
<b>Hand Crank Reels</b> Maximum Temperature 200 °C											
CT6050HN*	10	3/8	15	50	345	3/8	1/2	337	391	397	6
CT6100HN*	10	3/8	30	100	345	3/8	1/2	337	494	397	7.5
CM6050HN*	10	3/8	15	50	345	3/8	1/2 (M)	337	363	397	6.5
CM6100HN*	10	3/8	30	100	345	3/8	1/2 (M)	337	465	397	8
H18006 M118	10	3/8	30	100	345	1/2	1/2	425	349	511	14
CA38106 M118	10	3/8	43	140	345	1/2	1/2	425	483	514	19
CA38112 M118	10	3/8	91	300	345	1/2	1/2	425	635	514	21
<b>Spring Driven Reels</b> Maximum Temperature 200 °C											
PW7600 OHP118	10	3/8	15	50	345	1/2	1/2	483	178	514	20
PW7650 OHP118**	10	3/8	15	50	331	1/4	1/2	483	178	514	27
PW81000 OHP118	10	3/8	30	100	345	3/8	1/2	610	267	645	39

\*Maximum temperature 99 °C \*\*Hose included with this model; maximum temperature 100 °C

## Corrosion Resistant Reels

### Stainless Steel Series - 10, 13, 19 & 25mm I.D.

Stainless steel hose reels are ideal for food processing, pre-rinse, wash down, chemical transfer and industrial solvent handling. Swivels include Viton® O-rings. Hose and bumper not included.

Model w/out Hose	Hose I.D.		Hose Length		Pressure bar	(F)NPTF Reel Outlet in	(F)NPTF Reel Inlet in	Dimensions (mm)			Shipping Weight kg
	mm	in	mtr	ft				Length	Width	Height	
LC607 OLS-S70	10	3/8	21	70	21	3/8 BSPT	3/8 BSPT	492	206	521	16
LC807 OLS-S70	13	1/2	21	70	21	1/2 BSPT	1/2 BSPT	492	206	521	16
7600 OMS55	10	3/8	20	66	207	3/8	3/8	483	146	514	19
7800 OLS	13	1/2	15	50	35	1/2	1/2	483	146	514	19
7800 OMS	13	1/2	15	50	207	1/2	1/2	483	146	514	20
81000 OLS	10	3/8	30	100	35	3/8	3/8	610	257	645	37
82000 OLS	13	1/2	30	100	35	1/2	1/2	610	257	645	37
82000 OMS	13	1/2	23	75	103	1/2	1/2	610	257	645	38
83000 OLS70	19	3/4	15	50	35	3/4 BSPT	3/4 BSPT	610	257	645	37
83000 OMS70	19	3/4	15	50	86	3/4 BSPT	3/4 BSPT	610	257	645	38
D83000 OLS70	19	3/4	23	75	35	3/4 BSPT	3/4 BSPT	610	362	645	38
D84000 OLS70	25	1	15	50	35	1 BSPT	1 BSPT	610	387	645	42
HS18000 M	13	1/2	61	200	207	1/2	1/2	508	464	483	16
HS28000 M	13	1/2	91	300	207	1/2	1/2	508	464	483	16
HS19000 M	19	3/4	23	75	207	3/4 BSPT	3/4 BSPT	508	464	483	17
HS29000 M	19	3/4	38	125	207	3/4 BSPT	3/4 BSPT	508	464	483	16
HS37000 L70	25	1	30	100	35	1 BSPT	1 BSPT	534	800	572	21



LC607 OLS-S70



HS18000 M


## Air / Water / Chemical Delivery Reels

### SG Series - 10 & 13mm I.D.

The SG Series is economical, lightweight and easy to handle. This reel is made of corrosion proof, tough polypropylene and extensive tests have shown it to be highly resistant to the vast majority of acids, alkalis and UV Rays. Wall or floor mount. Hose included.

Model w/ Hose	Hose I.D.		Hose Length		Pressure bar	(M)NPTF Hose Outlet in	(F)NPTF Reel Inlet in	Dimensions (mm)			Shipping Weight kg
	mm	in	mtr	ft				Length	Width	Height	
<b>Air* &amp; Water* Hose Reels</b> Working Temperature 65 °C											
SGA3665 OLP	10	3/8	20	65	16	3/8	3/8	489	232	492	11
SGA3850 OLP	13	1/2	15	50	16	1/2	1/2	489	232	492	10
<b>Hot Water Wash Reel</b> Working temperature 85 °C. **Maximum working pressure at 30 °C.											
SHA3850 OLP	13	1/2	15	50	17**	1/2	1/2	489	232	492	10

\*Air hose can be used for water on these models.



SGA3665 OLP



Models listed with an icon are planned stock and should be able to ship same day or next day.