

Power and Light Cord Reels | Series L 4000 / L 5000 / L 7000 / L 70000



NEW!

L 70100 123 3A

Made in USA



L 4545 123 9G

Cord Options

| | |
|---------------------------------|--|
| | #3 - Single Receptacle Single 15 AMP with clamp type strain relief for both 16 AWG and 12 AWG cord. NEMA 5-15R |
| | #3A - Single Receptacle Single 20 AMP. NEMA 5-20R |
| | #3B - Twist Lock Connector Single 20 AMP with twist lock connector. NEMA L5-20R |
| | #4 - R.V. Plug Male rubber plug used with recreational vehicles (RV's). |
| #7/7A/7B - Duplex Outlet Box"/> | #7/7A/7B - Duplex Outlet Box Duplex outlet box with flip-top lid. GFCI protection on #7 and 7A. |
| #9/9G - Triple Tap"/> | #9/9G - Triple Tap Molded triple tap. GFCI protection on #9G only. |
| X - Flying Lead"/> | X - Flying Lead Bare cord or cable endings and conduit box. |

| | Model with Cord | Cord Ending | Cord Specifications | | | | Volts | Amps | Shipping Weight | | Size Index # | | |
|----|-----------------|-------------------------------|---------------------|-----------------|---------|-----|-------|--------|-----------------|------|--------------|-----|----|
| | | | AWG | mm ² | # Cond. | ft | | | m | Type | | lbs | kg |
| QS | L 4035 163 3 | Single Receptacle | 16 | 1.33 | 3 | 35 | 11 | SJTOW | 125 | 13 | 25 | 11 | 1 |
| QS | L 4050 163 3 | Single Receptacle | 16 | 1.33 | 3 | 50 | 15 | SJTOW | 125 | 13 | 26 | 12 | 1 |
| QS | L 4545 123 3 | Single Receptacle | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 15 | 27 | 12 | 1 |
| QS | L 5550 123 3 | Single Receptacle | 12 | 3.32 | 3 | 50 | 15 | SJEOOW | 125 | 15 | 44 | 20 | 3 |
| QS | L 70075 123 3 | Single Receptacle | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 15 | 70 | 32 | 5 |
| QS | L 70100 123 3 | Single Receptacle | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 15 | 74 | 34 | 5 |
| QS | L 4545 123 3A | Single Receptacle | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 20 | 28 | 13 | 1 |
| QS | L 5550 123 3A | Single Receptacle | 12 | 3.32 | 3 | 50 | 15 | SJEOOW | 125 | 20 | 44 | 20 | 3 |
| QS | L 70075 123 3A | Single Receptacle | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 20 | 70 | 32 | 5 |
| QS | L 70100 123 3A | Single Receptacle | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 20 | 74 | 34 | 5 |
| | L 4545 123 3B | Twist Lock Connector | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 20 | 28 | 13 | 1 |
| | L 5550 123 3B | Twist Lock Connector | 12 | 3.32 | 3 | 50 | 15 | SJEOOW | 125 | 20 | 44 | 20 | 3 |
| | L 70075 123 3B | Twist Lock Connector | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 20 | 70 | 32 | 5 |
| | L 70100 123 3B | Twist Lock Connector | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 20 | 74 | 34 | 5 |
| | L 5750 103 4 | R.V. Plug | 10 | 5.37 | 3 | 50 | 15 | SOOW | 125 | 30 | 50 | 23 | 4 |
| QS | L 4545 123 7 | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 15 | 29 | 13 | 1 |
| QS | L 5550 123 7 | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 50 | 15 | SEOOW | 125 | 15 | 45 | 20 | 3 |
| QS | L 70075 123 7 | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 15 | 72 | 33 | 5 |
| QS | L 70100 123 7 | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 15 | 76 | 34 | 5 |
| IN | L 4545 123 7A | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 20 | 29 | 13 | 1 |
| IN | L 70075 123 7A | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 20 | 72 | 33 | 5 |
| QS | L 70100 123 7A | Duplex Outlet Box w/GFCI (F)* | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 20 | 76 | 34 | 5 |
| IN | L 4545 123 7B | Duplex Outlet Box | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 20 | 29 | 13 | 1 |
| IN | L 4050 163 9 | Triple Tap | 16 | 1.33 | 3 | 50 | 15 | SJEOOW | 125 | 13 | 26 | 12 | 1 |
| QS | L 4545 123 9 | Triple Tap | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 15 | 28 | 13 | 1 |
| QS | L 70075 123 9 | Triple Tap | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 15 | 71 | 32 | 5 |
| QS | L 70100 123 9 | Triple Tap | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 15 | 75 | 34 | 5 |
| IN | L 4545 123 9G | Triple Tap w/GFCI (F) | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 | 15 | 29 | 13 | 1 |
| IN | L 70075 123 9G | Triple Tap w/GFCI (F) | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 | 15 | 72 | 33 | 5 |
| IN | L 70100 123 9G | Triple Tap w/GFCI (F) | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 | 15 | 76 | 34 | 5 |

For indoor non-weather tight applications only. All models UL listed at 125 Volt 60 Hz single phase. *The GFCI Receptacle is designed to protect from line-to-ground shock hazards. The Ground Fault Circuit Interrupter does not protect against short circuits or overloads; this is the function of the fuse or circuit breaker. Reference page 4 for guide arm positions. **NOTE:** Swing brackets should be used if cords are pulled at more than 45°, see page 47.

| Flying Lead Model with Cord | Model No Cord | Cord Specifications | | | | Volts/ Amps | Volts/ Amps | Shipping Weight* | | Size Index # | | | |
|-----------------------------|---------------|---------------------|-----------------|---------|----|-------------|-------------|------------------|----------|--------------|-----|----|----|
| | | AWG | mm ² | # Cond. | ft | | | m | Type | | lbs | kg | |
| | L 4050 163 X | L 4000 | 16 | 1.33 | 3 | 50 | 15 | SJEOOW | 125 / 13 | 220 / 6.5 | 22 | 10 | 1 |
| | ----- | L 4100 | 16 | 1.33 | 4 | 50 | 15 | SJEOOW | 125 / 10 | 220 / 5 | 22 | 10 | 1 |
| IN | L 4545 123 X | L 4500 | 12 | 3.32 | 3 | 45 | 14 | SJEOOW | 125 / 20 | 220 / 10 | 22 | 10 | 1 |
| | ----- | L 5000 | 10 | 5.27 | 3 | 35 | 11 | SO | 125 / 30 | 220 / 15 | 29 | 13 | 2 |
| | ----- | L 5400 | 12 | 3.32 | 3 | 35 | 11 | SJEOOW | 125 / 13 | 220 / 6.5 | 25 | 11 | 2 |
| | L 5550 123 X | L 5500 | 12 | 3.32 | 3 | 50 | 15 | SEOOW | 125 / 20 | 220 / 10 | 35 | 16 | 3 |
| | L 70075 123 X | L 70075 | 12 | 3.32 | 3 | 75 | 23 | SEOOW | 125 / 20 | 220 / 10 | 69 | 31 | 6 |
| | L 70100 123 X | L 70100 | 12 | 3.32 | 3 | 100 | 30 | SEOOW | 125 / 20 | 220 / 10 | 73 | 33 | 6 |
| | L 5550 124 X | ----- | 12 | 3.32 | 4 | 50 | 15 | SEOOW | ----- | 600 / 16 | 44 | 20 | 3 |
| | L 70100 124 X | L 70100 124 | 12 | 3.32 | 4 | 100 | 30 | SEOOW | ----- | 600 / 16 | 75 | 34 | 6 |
| | L 5750 103 X | L 5700 | 10 | 5.27 | 3 | 50 | 15 | SEOOW | 125 / 30 | 220 / 15 | 37 | 17 | 4 |
| | ----- | L 7000 | 6 | 13.3 | 4 | 35 | 11 | SOOW | ----- | 220 / 45 | 41 | 19 | ** |
| | L 7050 104 X | ----- | 10 | 5.27 | 4 | 50 | 15 | SEOOW | ----- | 600 / 20 | 65 | 29 | ** |

For indoor non-weather tight applications only. All models UL listed at 125 Volt 60 HZ single phase. *Weight of model without cord. **Refer to reelcraft.com. Reference page 4 for guide arm positions.